

KERN PFB (SK)



Quick-display precision balance with user-friendly concept of operation and EC type approval [M]

Features

- **Concept of easy use:** All primary functions have their own key on the keypad
- **Compact size,** practical for small spaces
- **Capacity display:** A bar lights up to show how much of the weighing range is still available
- **Level indicator and foot screws** to level the balance precisely, fitted as standard, to give the most accurate weighing results
- **Draft shield** standard for models with weighing plate sizes **A** and **B**. Removable metal cover with pipette opening, weighing space WxDxH 158x143x64 mm

- **1 Separate second display** standard for models PFB 600-1M and PFB 6000-0M. Suitable for direct sales to the public. The verification value is the same as the readout. Large backlit LCDdisplay, Digit height 16 mm. Interface cable to the balance, Cable length approx. 1 m, standard. Dimensions WxDxH 250x180x105 mm

Technical data

- Backlit LCD display, digit height 15 mm
- Dimensions of weighing plate (stainless steel)
A Ø 80 mm, **B** Ø 120 mm
C WxD 155x145 mm, see larger picture

- Overall dimensions (without draft shield) WxDxH 200x190x87 mm
- Net weight approx. 2 kg
- Permissible ambient temperature 5 °C / 35 °C

Accessories

- **2 Separate second display,** ideal for training and demonstration purposes in laboratories or in industry, not permitted for direct sales to the public, KERN PFB-A08
- **Suitable printers** see page 138

STANDARD



OPTION



FACTORY






































Model	Weighing range [Max] g	Readout [d] g	Verific. value [e] g	Reproducibility g	Linearity g	Weighing plate	Options			
							Verification		DKD Calibr. Certificate	
							M II	KERN	DKD	KERN
PFB 120-3	120	0,001	-	0,001	± 0,003	A	-	-	963-127	
PFB 200-3	200	0,001	-	0,001	± 0,003	A	-	-	963-127	
PFB 300-3	300	0,001	-	0,002	± 0,003	A	-	-	963-127	
PFB 1200-2	1200	0,01	-	0,01	± 0,03	B	-	-	963-127	
PFB 2000-2	2000	0,01	-	0,01	± 0,03	B	-	-	963-127	
PFB 3000-2	3000	0,01	-	0,01	± 0,03	B	-	-	963-127	
PFB 6K0.05	6000	0,05	-	0,05	± 0,15	C	-	-	963-128	
PFB 6000-1	6000	0,1	-	0,1	± 0,3	C	-	-	963-128	

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.

PFB 600-2M	600	0,01	0,1	0,01	± 0,02	B	965-216	963-127
PFB 600-1M	600	0,1	0,1	0,1	± 0,1	B	965-216	963-127
PFB 6000-1M	6000	0,1	1	0,1	± 0,3	C	965-217	963-128
PFB 6000-0M	6000	1	1	1	± 1	C	965-217	963-128

KERN Pictograms

 Internal adjusting (CAL): Quick setting of the balance's accuracy with internal adjusting weight (motordriven).	 Recipe level A: Separate memory for the weight of the tare container and the recipe ingredients (net total).	 Rechargeable battery pack: rechargeable set.
 Adjusting program (CAL): For quick setting of the balance's accuracy. External adjusting weight required.	 Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through displays.	 Mains adapter: 230V/50Hz in standard version for Germany. On request GB, AUS or USA version.
 Memory: Balance contains memories, e.g. for item data, weighing data, tare weights etc. PLU.	 Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through displays. Additional convenient functions, such as barcode and back calculation functions.	 Power supply: integrated in balance. 230V/50Hz in Germany. More standards e. g. GB, AUS, USA on request.
 Data interface RS-232: To connect the balance to a printer, PC or network.		 Strain gauges: Electrical resistor on an elastic deforming body.
 RS 485 data interface: To connect the balance to a printer, PC or other peripheral devices. High tolerance against electromagnetic disturbance.	 Percentage determination: Determining the deviation in % from the target value (100%).	 Tuning fork principle: A resonating body is electromagnetically excited, causing it to oscillate.
 USB data interface: To connect the balance to a printer, PC or other peripheral devices.	 Weighing units: Can be switched to e. g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.	 Electromagnetic force compensation: Coil in a permanent magnet. For the most accurate weighings.
 Bluetooth data interface: To transfer data from the balance to a printer, PC or other peripheral devices.	 Weighing with tolerance range: Upper and lower limiting can be programmed individually, e.g. dosing/sorting and portioning.	 Single cell technology: Advanced version of the force compensation principle with the highest level of precision.
 Control outputs (optocoupler, digital I/O): to connect relays, signal lamps, valves, etc.	 Vibration-free weighing: (Animal weighing program) Vibrations are filtered out so that a stable weight is obtained.	 Verification possible: The time required for verification is specified in the pictogram.
 Interface for second balance: for direct connection of a second balance.	 Spray and dust protection IPxx: The type of protection is shown by the pictogram. For details see the glossary.	 DKD calibration possible: The time required for DKD calibration is shown in days in the pictogram.
 Network interface: For connecting the scale to an Ethernet network. With KERN products you can also use a universal RS-232/LAN converter.	 Stainless steel: the balance is protected against corrosion.	 Package shipment: The time required to manufacture the product internally is shown in days in the pictogram.
 GLP/ISO record keeping: of weighing data with date, time and identification-no. Only with printers from KERN.	 Suspended weighing: load support with hook on the underside of the balance.	 Pallet shipment: The time required to manufacture the product internally is shown in days in the pictogram.
 Piece counting: Reference quantities selectable. Display can be switched from piece to weight.	 Battery operation: Ready for battery operation. The battery type is specified for each device.	 Warranty: The warranty period is shown in the pictogram.

Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight package for your balance, consisting of the test weight, box and DKD certificate, as proof of its accuracy ... the best pre-requisite for proper balance calibration.

In the extensive KERN test weight range, you will find test weights in the international OIML error limit classes: E1, E2, F1, F2, M1, M2, M3 with weights from 1 mg - 2000 kg.

The KERN DKD calibration laboratory for electronic balances and weights has been accredited by DKD since 1994 and today is one of the most modern and best-equipped DKD calibration laboratories for balances, test weights and force-measurement in Europe.

(DKD = German Calibration Service)

Thanks to the high level of automation, we can carry out DKD calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DKD calibration of balances with a maximum load of up to 6 t
- DKD calibration of weights in the range of 1 mg – 500 kg
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DKD calibration certificates in the following languages
D, GB, F, I, E, NL, PL

Do you have questions about your scale, the corresponding test weight or the calibration service? Your KERN specialist dealer will be pleased to assist you.

Your KERN specialist dealer: